

LP 300™

For Heavier Crude Oil

Background

LP 300 Flow Improver is part of ConocoPhillips Specialty Products' range of innovative and technologically superior Flow Improver Solutions. As part of the portfolio, LP 300 Flow Improver has been designed specifically for heavier types of crude.

Characteristics

LP 300 Flow Improver is an aqueous suspension product with a greater affinity for heavier crudes. Like our other LP Flow Improvers, it can provide greater than 80% drag reduction.

Benefits

Great performance

- Designed specifically to increase performance in heavier crudes
- Great heat stability in tropical and desert environments
- Greater than 80% drag reduction
- Increases flow rates while maintaining current pipeline pressures
- Maintains flow while reducing pipeline pressures
- Allows shutting down of intermediate pump stations

Superior technology

- Improves pipeline capacity without capital investment
- Less polymer required to achieve a given performance
- Lower injection rates than other drag reducers
- Faster dissolution rates than traditional drag reducers
- Reduces internal corrosion rate by 40%
- Reduces crude heat loss


LP 300 Flow Improver allows companies to strategically reduce pipeline operating costs, increase throughput, decrease pressure or shut down intermediate pump stations.

LP 300 Flow Improver offers the same advanced polymer technology as other LP Flow Improvers. It dissolves into flowing product without coating pipeline walls, and increases throughput while reducing internal corrosion rates. It allows greater amounts of active polymer to be deployed in a fixed amount of product while improving dissolution dynamics. The polymer of choice offers excellent hydrocarbon affinity, and is able to attain elevated levels of drag reduction under varied operating scenarios. It also has the strength to effectively endure shear forces.

Handling

LP 300 Flow Improver is easy to handle, store and clean up. It is environmentally friendly and non-flammable. It flows easily and does not require nitrogen pressurized storage tanks.

See back page for product properties



The performance curve shows the performance range in which LP 300 Flow Improver operates, depending on pipeline and crude conditions.

Contact us at www.LiquidPower.com

PRODUCT PROPERTIES

GENERAL	
Designed for use on	Heavier Petroleum Crude Oil
Flow Improver type	Suspension
Carrier/Solvent	Water
PERFORMANCE	
Maximum drag reduction	Greater than 80%
Typical concentration	5 to 50 ppm
TYPICAL PROPERTIES	
Color	White
Density	8.0 lbs/gal (0.96 g/cm ³)
Flash Point	Not applicable
Viscosity	400 cP @ 511s ⁻¹ (Non-Newtonian)
Freezing Point	32°F (0°C)
Boiling Point	212°F (100°C)
Vapor Pressure	0.95 lb/in ² (24 mm Hg @ 25°C)
HANDLING	
Operating range	32°F to 120°F (0°C to 48.9°C)
Product stability	Stable suspension Intermittent agitation recommended
Pressure	No nitrogen or pressurized vessels required
Heating	Climate control environment available
INJECTION EQUIPMENT	
Pumps	Various designs available for different injection range and environments
Range	5 to 2,500 gal/day (20 to 9,500 L/day)
Flow meter	Mass (Coriolis)
Automation	Available
SAFETY AND ENVIRONMENTAL (See Material Safety Data Sheet)	
Safety	Non-hazardous, non-flammable
Health	Low toxicity. Conventional protection equipment
Environmental	Very low aquatic toxicity

The data presented is based on test results and experiences that ConocoPhillips believes reliable and are supplied for information purposes only. ConocoPhillips disclaims any liability, damage or injury that results from the use of the data and nothing contained herein shall constitute a guarantee, warranty or representation (including freedom from patent liability) by ConocoPhillips with respect to the data, the products described or their use for any specific purpose, even if that purpose is known to ConocoPhillips.

North America
Latin America
 P.O. Box 2197
 Houston, TX 77252-2197
 USA
 Tel: +1.832.486.2834
 +1.800.897.2774 (USA Toll Free)
 Fax: +1.832.486.2881

**Europe, Middle East, Africa
 and Asia Pacific**
 Mediaalaan 50
 1800 Vilvoorde
 Brussels
 Belgium
 Tel: +32.2.263.0520
 Fax: +32.2.267.5176

Russia and CIS
 1st Brestskaya str. 29, 8th Floor
 Moscow, Russia 125047
 Tel: +7.095.785.2859
 Fax: +7.095.785.2803