

SAFETY DATA SHEET

1. Identification

Product identifier EP™ 2000 Flow Improver

Other means of identification None.

Recommended use Flow Improver.

Recommended restrictions Other uses are not recommended unless an assessment demonstrates potential exposures will be

controlled.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer LiquidPower Specialty Products Inc.

Address 2103 CityWest Blvd.

Suite 1400

Houston, TX 77042

Telephone 1.713.339.8703 or 1.800.897.2774

e-mail SDS@LiquidPower.com
Website www.LiquidPower.com
Emergency telephone +1 703.527.3887

+1 800.424.9300

2. Hazard identification

Physical hazards Not classified.

Health hazards Specific target organ toxicity following

repeated exposure

Environmental hazards Hazardous to the aquatic environment,

long-term hazard

Label elements



Signal word Warning

Hazard statement May cause damage to organs (kidneys) through prolonged or repeated exposure. Harmful to

Category 2 (kidneys)

Category 3

aquatic life with long lasting effects.

Precautionary statement

Prevention Do not breathe mist or vapour. Avoid release to the environment.

Response Get medical advice/attention if you feel unwell.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental information None.

Other hazards None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Non-Hazardous Materials		Various	60 - 80
Ethylene glycol		107-21-1	10 - 30
C11-C15 Hydrocarbon Solvent 1*		Proprietary*	3 - 7
C11-C15 Hydrocarbon Solvent 2*		Proprietary*	3 - 7
Sodium lauryl sulfate		151-21-3	0.5 - 1.5

EP™ 2000 Flow Improver SDS Canada

Surfactant

Chemical name	Common name and synonyms	CAS number	%
Alcohols, C12 - C14 secon	dary, ethoxylated	84133-50-6	1- 5
Alcohol Ethoxylate*		Proprietary*	1- 5

^{*} See Section 15 for HMIRA status.

Composition comments

Total hydrocarbon solvents concentration <7%. Total alcohol ethoxylate concentration <6%.

All concentrations are in percent by weight. Components not listed are either non-hazardous or are below reportable limits.

4. First-aid measures

Inhalation

Get medical attention if discomfort persists.

Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact

Flush thoroughly with water. If irritation occurs, get medical assistance.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

effects.

symptoms/effects, acute and delaved

Indication of immediate

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

Direct contact with eyes may cause temporary irritation. Prolonged exposure may cause chronic

medical attention and special treatment needed

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted. General fire hazards

6. Accidental release measures

Personal precautions,

protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapour. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Do not breathe mist or vapour. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

2/8

EP™ 2000 Flow Improver SDS Canada Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. ACGIH Threshold Limit Values Components	Туре	Value	Form
C11-C15 Hydrocarbon Solvent 1*	TWA	200 mg/m3	Non-aerosol.
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction

		00 PP	rapo. naonon	
	TWA	25 ppm	Vapor fraction	
Canada. Alberta OELs (Occupa Components	tional Health & Safety Code, Sch Type	nedule 1, Table 2) Value	Form	
C11-C15 Hydrocarbon Solvent 1*	TWA	200 mg/m3	Vapour.	
Ethylene glycol (CAS 107-21-1)	Ceiling	100 mg/m3		

Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended)

Components	Туре	Value	Form	
C11-C15 Hydrocarbon Solvent 1*	TWA	200 mg/m3	Non-aerosol.	
Ethylene glycol (CAS 107-21-1)	Ceiling	100 mg/m3	Aerosol	
		50 ppm	Vapour.	
	STEL	20 mg/m3	Particulate.	
	TWA	10 mg/m3	Particulate.	

Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act)

Components	Туре	Value	Form
C11-C15 Hydrocarbon Solvent 1*	TWA	200 mg/m3	Non-aerosol.
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.
		50 ppm	Vapor fraction
	TWA	25 ppm	Vapor fraction

Canada. New Brunswick OELs: Threshold Limit Values (TLVs) Based on the 1991 and 1997 ACGIH TLVs and BEIs Publication (New Brunswick Regulation 91-191)

Components	Туре	Value	Form
Ethylene glycol (CAS	Ceiling	100 mg/m3	Aerosol

Value

Form

Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents)

Components	туре	value	Folili
C11-C15 Hydrocarbon Solvent 1*	TWA	200 mg/m3	Non-aerosol.
Ethylene glycol (CAS 107-21-1)	STEL	10 mg/m3	Aerosol, inhalable.

Canada. Quebec OELs. (Ministry of Labor - Regulation respecting occupational health and safety)

Components	Туре	Value	Form
Ethylene glycol (CAS 107-21-1)	Ceiling	127 mg/m3	Vapor and mist.
		50 ppm	Vapor and mist.

EP™ 2000 Flow Improver SDS Canada

Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) **Form** Components Value Type C11-C15 Hydrocarbon 15 minute 250 mg/m3 Vapour. Solvent 1* 8 hour 200 ma/m3 Vapour. Ceiling 100 mg/m3 Ethylene glycol (CAS Aerosol 107-21-1)

Biological limit values No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Canada - Alberta OELs: Skin designation

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

Can be absorbed through the skin.

Canada - British Columbia OELs: Skin designation

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

Can be absorbed through the skin.

Canada - Manitoba OELs: Skin designation

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

Danger of cutaneous absorption

Canada - Ontario OELs: Skin designation

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*) Can be absorbed through the skin.

Canada - Saskatchewan OELs: Skin designation

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

Can be absorbed through the skin.

US ACGIH Threshold Limit Values: Skin designation

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

Danger of cutaneous absorption

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Normal work clothing (long sleeved shirts and long pants) is recommended.

Respiratory protection In case of accident and/or inadequate ventilation, use respiratory protection with organic vapour

cartridge.

Thermal hazards Not applicable.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColourWhite.

Odour Mild petroleum odour.
Odour threshold No data available.

pH 6 - 9

Melting point/freezing point -22.78 °C (-9 °F)
Initial boiling point and boiling 105.56 °C (222 °F)

range

Flash point > 93.33 °C (> 200 °F) Pensky-Martens Closed Cup ASTM D93, EPA 1010

Evaporation rate Same as water.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) No data available.

EP™ 2000 Flow Improver SDS Canada

Explosive limit - upper

(%)

No data available.

Vapour pressure 24 mm Hg @ 100°F / 37.8°C (estimate)

Vapour density < 1

Relative density 0.97 - 1.03 (25°C / 77°F)

Solubility(ies)

Disperses completely. Solubility (water)

Partition coefficient (n-octanol/water)

Not available.

No data available. **Auto-ignition temperature**

Decomposition temperature No data available.

Viscosity 85 cP @ 511s-1 @ 77°F (Non-newtonian).

Other information

Bulk density Not determined. **Explosive properties** Not explosive. **Oxidising properties** Not oxidising. Particle size Not applicable. Percent volatile No data available.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Material is stable under normal conditions. **Chemical stability**

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Avoid temperatures exceeding the flash point. Contact with incompatible materials.

Strong oxidising agents. Incompatible materials

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation No adverse effects due to inhalation are expected. Skin contact Prolonged skin contact may cause temporary irritation. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Under normal conditions of intended use, this material does not pose a risk to health. However:

> Ingestion of ethylene glycol may result in nausea, vomiting, abdominal cramps, blindness, liver damage, irritation, reproductive effects, nerve damage, convulsions, edema of the lung, cardiopulmonary effects (metabolic acidosis), pneumonia and kidney failure which could result in death. The single lethal dose of ethylene glycol for humans is about 100 ml. Inhalation of high

levels of vapors or mists for prolonged periods of time may also result in toxic effects.

Symptoms related to the physical, chemical and toxicological characteristics

Direct contact with eyes may cause temporary irritation.

Information on toxicological effects

May be harmful if swallowed. Acute toxicity

Components **Species Test Results**

Ethylene glycol (CAS 107-21-1)

Acute Dermal

LD50 Rabbit 9530 mg/kg

Sodium lauryl sulfate (CAS 151-21-3)

Acute

Oral

LD50 Rat 1200 mg/kg

EP™ 2000 Flow Improver SDS Canada

Skin corrosion/irritation

Serious eye damage/eye

irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitisation

Canada - Alberta OELs: Irritant

Ethylene glycol (CAS 107-21-1) Irritant

Respiratory sensitisation

No information available on the mixture. However, none of the components are classified in respect of this hazard (or are present at a level below the concentration threshold for

classification).

Skin sensitisationNo information available on the mixture. However, none of the components are classified in

respect of this hazard (or are present at a level below the concentration threshold for

classification).

Germ cell mutagenicity

No information available on the mixture. However, none of the components are classified in

respect of this hazard (or are present at a level below the concentration threshold for

classification).

Carcinogenicity No information available on the mixture. However, none of the components are classified in

respect of this hazard (or are present at a level below the concentration threshold for

classification).

ACGIH Carcinogens

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

A3 Confirmed animal carcinogen with unknown relevance to

humans.

Ethylene glycol (CAS 107-21-1)

A4 Not classifiable as a human carcinogen.

Canada - Manitoba OELs: carcinogenicity

Ethylene glycol (CAS 107-21-1)

C11-C15 Hydrocarbon Solvent 1* (CAS Proprietary*)

Confirmed animal carcinogen with unknown relevance to humans.

Not classifiable as a human carcinogen.

Reproductive toxicity

No information available on the mixture. However, none of the components are classified in respect of this hazard (or are present at a level below the concentration threshold for

classification).

Specific target organ toxicity -

single exposure

No information available on the mixture. However, none of the components are classified in

respect of this hazard (or are present at a level below the concentration threshold for

classification).

Specific target organ toxicity -

repeated exposure

May cause damage to organs (kidneys) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Chronic effects Prolonged exposure may cause chronic effects.

Further information Ingestion of ethylene glycol may result in nausea, vomiting, abdominal cramps, blindness, liver

damage, irritation, reproductive effects, nerve damage, convulsions, oedema of the lung, cardiopulmonary effects (metabolic acidosis), pneumonia and kidney failure which could result in death. The single lethal dose for humans is about 100 ml. Inhalation of high levels of vapour or

mists for prolonged periods of time may also result in toxic effects.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Components		Species	Test Results
Ethylene glycol (CAS	107-21-1)		
Aquatic			
Acute			
Crustacea	EC50	Ceriodaphnia dubia	10000 mg/l, 48 Hours
Fish	LC50	Oncorhynchus mykiss	24591 mg/l, 96 Hours
Chronic			
Crustacea	NOEC	Ceriodaphnia dubia	3469 mg/l, 7 days
Fish	NOEC	Oncorhynchus mykiss	14692 mg/l, 12 days
Sodium lauryl sulfate	(CAS 151-21-3)		
Aquatic			
Acute			
Algae	EC50	Scenedesmus subspicatus	36.5 mg/l, 72 Hours

EP™ 2000 Flow Improver SDS Canada

Components **Species Test Results** Crustacea EC50 Ceriodaphnia dubia 5.55 mg/l, 48 Hours LC50 Fish Lepomis macrochirus 4.5 mg/l, 96 Hours

Persistence and degradability

Not expected to persist in the environment if spilled or released.

The product is not expected to bioaccumulate. Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylene glycol (CAS 107-21-1) -1.36Sodium lauryl sulfate (CAS 151-21-3) 1.6

Mobility in soil Expected to have low mobility in soil and sediments with adsorption being the predominant

physical process.

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation Other adverse effects

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow **Disposal instructions**

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations. Waste material from this product should not be exposed to waste streams or sumps containing any concentration of hydrocarbon. This will cause

formation of gelled substances that may plug pipes.

Local disposal regulations

Dispose in accordance with all applicable regulations. Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and

the IBC Code

Not established.

15. Regulatory information

Canadian regulations This product has been classified in accordance with the hazard criteria of the HPR and the SDS

contains all the information required by the HPR.

HMIRA Registry Number 12272

WHMIS Trade Secret Registration Filing Date: 2018-10-24

WHMIS Trade Secret Decision Granted Date: 2023-03-27

Controlled Drugs and Substances Act

Not regulated.

Export Control List (CEPA 1999, Schedule 3)

Not listed.

Greenhouse Gases

Not listed.

Precursor Control Regulations

Not regulated.

International regulations

EP™ 2000 Flow Improver

Version #: 04 Revision date: 29-March-2023 937406 Issue date: 25-April-2017 7/8

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto Protocol

Not applicable.

Montreal Protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Industrial Chemicals (AICIS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances	Yes

(PICCS)

Taiwan Taiwan Chemical Substance Inventory (TCSI) No United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory Yes

16. Other information

Issue date 25-April-2017 **Revision date** 29-March-2023

Version No. 04

List of abbreviations LD50: Lethal Dose, 50%.

Version #: 04 Revision date: 29-March-2023

LC50: Lethal Concentration, 50%. EC50: Effective Concentration, 50%. NOEC: No observed effect concentration. vPvB: very Persistent, very Bioaccumulative.

TWA: Time weighted average. STEL: Short term exposure limit.

HSDB® - Hazardous Substances Data Bank References

IARC Monographs. Overall Evaluation of Carcinogenicity

LiquidPower Specialty Products Inc. cannot anticipate all conditions under which this information Disclaimer

and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Issue date: 25-April-2017

937406

8/8

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).